

Bridgeport (BT) Series



advantage: ergonomic functionality | use: clean room, static control/ESD, various workspaces

Bridgeport Series chairs boast a number of benefits that make them popular choices for education, healthcare, laboratories, industrial, office and other workspaces: ergonomic functionality and a streamlined backrest. 13-year warranty.

- Cloth and vinyl upholstery styles available to match various workspace requirements.
- Ergonomically designed concave seat with internal seat board bumperguard.
- Black powder-coat finish standard on metal parts. Optional chrome or custom powder-coat colors available.
- Pneumatics are available to provide low, medium and high seat height ranges to accommodate many task requirements.
- High-profile Euro-look base with T-shape construction for added strength and easy cleanability.
- Dual-wheel non-marring polyurethane casters resist movement when the chair is unoccupied, enhancing workplace safety by inhibiting seating from rolling away.

Shown here:
Bridgeport Series
with R base, low
seat height range

ordering information | january 2024

● = 2-Day Shipping

Bridgeport Series | Standard Components

18.5"W x 16.5"D x 3"T seat, 14.5"W x 9.5"H backrest with lumbar support and plastic protective panel, soft touch pneumatic seat height adjustment; fixed rearward 3.5° seat tilt; backrest tilt and backrest height adjustment, grade 2 upholstery

Models with tubular steel base

Model#	Seat-Hgt.	Compatibility
● BTS-L-RC-T-XF-XA-06	Low, 18"-22"	Desk
● BTS-M-RC-T-XF-XA-06	Medium, 21"-28"	Standard Bench
● BTS-H-RC-T-XF-XA-06	High, 25"-32"	High Bench

Models with cast aluminum base

Model#	Seat-Hgt.	Compatibility
● BTA-L-RC-T-XF-XA-06	Low, 17"-22"	Desk
● BTA-M-RC-T-XF-XA-06	Medium, 19"-26"	Standard Bench
● BTA-H-RC-T-XF-XA-06	High, 22"-32"	High Bench

Models with reinforced composite base

Model#	Seat-Hgt.	Compatibility
● BTR-L-RC-T-XF-XA-06	Low, 17"-22"	Desk
● BTR-M-RC-T-XF-XA-06	Medium, 19"-26"	Standard Bench
● BTR-H-RC-T-XF-XA-06	High, 22"-32"	High Bench

Models with wide aluminum base

Model#	Seat-Hgt.	Compatibility
● BTW-H-RC-T-XF-XA-06	High, 22"-32"	High Bench

Ask about special and custom orders.

WARNING: This product can expose you to chemicals including wood dust, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.



- 23" diameter tubular steel (S style) base with 21" diameter affixed footring.



- 25.6" diameter, high-profile cast aluminum (A style) base.



- 25.6" diameter, high-profile reinforced composite (R style) base.



- 28.7" diameter, high-profile wide aluminum (W style) base.

optional components			● = 2-Day Shipping
Component	MFG Code	Description	
Seat	● E	Ergonomic with 4-way contouring and internal seat board bumperguard, 18.5"W x 17"D x 3"T	
	A	Saddle-shaped, contoured, waterfall front, 21"W x 19"D x 3"T; <i>call factory for pricing when selected with a performance package</i>	
Armrest	ARS	Height/width adjustable with self-skinned urethane pads (<i>not available with ISO 3 or 4 performance packages</i>)	
	● PSAS	Height adjustable with self-skinned urethane pads	
Seat Control	● FFAC	Free float articulating: pneumatic seat- and backrest-height adjustment; seat and backrest tilt independently via separate levers, and can free float or lock into place, seat can tilt forward ISO 5 performance package configurations	
	EXE	Executive tilt: pneumatic seat- and backrest-height adjustment; backrest tilt; seat and backrest swivel tilt in unison; tilt tension control knob and single lever seat tilt lock into any position (<i>only available on models with maximum seat height of 26" or less</i>)	
	ASC	Articulating Seat Control: Pneumatic seat- and backrest-height adjustment; seat and backrest tilt independently and lock into place with a single lever (<i>only available on ISO 3 and ISO 4 clean room models without arms</i>)	
Footring	● AFP	Adjustable height, 22" diameter, oval tube construction, solid polished cast aluminum spoke (<i>recommended for medium and high height models with A, W or R bases, adjusts easily without knobs/levers; not available with low height models or S style base units</i>)	
	● ATF	Adjustable height, 20" diameter, cast aluminum (<i>recommended for medium and high height models with A, W or R bases, not available with low height models or S style base units</i>)	
Glides	● HG	2" high polyamide glides	
Casters	LRO	Dual-wheel, soft tread, with weight-activated self-braking capability; resists movement when seat is occupied	
	R	Single-wheel, thermoplastic rubber, non-marring, ball-bearing construction; for hard floors including concrete	
	● RC	Hooded dual-wheel, non-marring resistance casters, resist movement when seat is unoccupied – standard on most models	
	RK	Hooded dual-wheel, non-marring resistance casters for ESD applications; resist movement when seat is unoccupied (<i>standard with ESD performance packages</i>)	
Miscellaneous	SW	Skid wrapping, net cost per pallet	
	VU	Upholstered underwrap to match seat upholstery	

upholstery	
MFG Code	Description
COM	Customer's own material
Grade 2	Comes standard on upholstered models unless otherwise noted
Grade 3	Grade 3 upholstery
Grade 4	Grade 4 upholstery
Grade 5	Grade 5 upholstery

performance packages		
Category	Class	MFG Code
ESD	—*	K
Clean Room	ISO 8**	ISO8
	ISO 7**	ISO7
	ISO 6	ISO6
	ISO 5	ISO5
	ISO 4*	ISO4
	ISO 3*	ISO3
Clean Room/ESD	ISO 8/ESD*	ISO8K
	ISO 7/ESD*	ISO7K
	ISO 6/ESD*	ISO6K
	ISO 5/ESD*	ISO5K
	ISO 4/ESD*	ISO4K
	ISO 3/ESD*	ISO3K
Standard black metal part finish	—	06
Chrome-plated metal parts, chairs w/A, W, R base	—	● C
Chrome-plated metal parts, chairs w/S base	—	● C

*Not available with R style base.
**Comes standard with black powder coat metal finish.

