

UniqueU (UU) Series

advantage: versatility | use: clean room, static control/ESD, various workspaces

These durable urethane chairs have easy-to-clean seats and backrests that resist water, chemicals, paints and more. The versatile ergonomic seating is designed to meet clean room and ESD demands and functional design requirements. 13-year warranty.



Shown here:
UniqueU Series
with **A** base,
low seat
height range

ordering information | january 2024

● = Next Day Shipping ● = 2-Day Shipping

UniqueU Series | Standard Components

18.5"W x 17"D x 1.5"T seat, 16.5"W x 12.5"H backrest with ventilating ribs and integral lumbar support, soft touch pneumatic seat height adjustment, fixed rearward 3.5° seat tilt, backrest tilt and backrest height adjustment

Models with tubular steel base

Model#	Seat-Hgt.	Compatibility
● UUS-L-RC-T-XF-XA-06	Low, 17"-21"	Desk
● UUS-M-RC-T-XF-XA-06	Medium, 20"-27"	Standard Bench
● UUS-H-RC-T-XF-XA-06	High, 24"-31"	High Bench

Models with cast aluminum base

Model#	Seat-Hgt.	Compatibility
● UUA-L-RC-T-XF-XA-06	Low, 16"-21"	Desk
● UUA-M-RC-T-XF-XA-06	Medium, 18"-25"	Standard Bench
● UUA-H-RC-T-XF-XA-06	High, 21"-31"	High Bench

Models with reinforced composite base

Model#	Seat-Hgt.	Compatibility
● UUR-L-RC-T-XF-XA-06	Low, 16"-21"	Desk
● UUR-M-RC-T-XF-XA-06	Medium, 18"-25"	Standard Bench
● UUR-H-RC-T-XF-XA-06	High, 21"-31"	High Bench

Models with wide aluminum base

Model#	Seat-Hgt.	Compatibility
● UUW-L-RC-T-XF-XA-06	Low, 16"-21"	Desk
● UUW-M-RC-T-XF-XA-06	Medium, 18"-25"	Standard Bench
● UUW-H-RC-T-XF-XA-06	High, 21"-31"	High Bench

Ask about special and custom orders.



- 23" diameter tubular steel (S style) base with 21" diameter affixed footring.



- 25.6" diameter, high-profile cast aluminum (A style) base.



- 25.6" diameter, high-profile reinforced composite (R style) base.



- 28.7" diameter, high-profile wide aluminum (W style) base.



optional components			● = Next Day Shipping ● = 2-Day Shipping
Component	MFG Code	Description	
Seat Controls	● FFAC	Free float articulating pneumatic: seat- and backrest-height adjustment; seat and backrest tilt independently via separate levers, and can free float or lock into place; seat can tilt forward	
Armrests	ARS	Height/width adjustable with self-skinned urethane pads (Not available with FFAC seat control)	
Footring	● AFP	Adjustable height, 22" diameter, oval tube construction on solid polished cast aluminum spoke (Adjusts easily without knobs or levers, not available with low height models or units with S style base)	
	● ATF	Adjustable height, 20" diameter, cast aluminum (recommended for medium and high height models with A, W or R bases. Not available with low height models or units with S style base)	
Glides	● HG	2" high polyamide glides	
Casters	LRO	Dual-wheel, soft tread, with weight-activated self-braking capability; resists movement when seat is occupied	
	R	Single-wheel, thermoplastic rubber, non-marring, ball-bearing construction; for hard floors including concrete	
	● RC	Hooded dual-wheel, non-marring resistance casters, resist movement when seat is unoccupied – standard on most models	
	RK	Hooded dual-wheel, non-marring resistance casters for ESD applications; resist movement when seat is unoccupied (standard with ESD performance packages)	
Miscellaneous	SW	Skid wrapping, net cost per pallet	

performance packages		
Category	Class	MFG Code
ESD	—*	K
Clean Room	ISO 8**	ISO8
	ISO 7**	ISO7
	ISO 6	ISO6
Clean Room/ESD	ISO 8/ESD*	ISO8K
	ISO 7/ESD*	ISO7K
	ISO 6/ESD*	ISO6K
Chrome-plated metal parts chairs w/A, W, R base	—	● C
Chrome-plated metal parts chairs w/S base	—	● C

*Not available with R style base.

**Comes standard with black powder coat metal finish.

⚠ WARNING: This product can expose you to chemicals including wood dust, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

