




Grey

Grounding & Cleaning

If the material is used on top of an already properly grounded surface, [grounding hardware](#) may not be necessary. Where no properly grounded surface is available, [grounding hardware](#) is required to provide a path-to-ground. Rtg compliance verification measurements must be made as outlined in ESD TR53 with a [surface resistance meter](#).

See Tech Bulletin [TB-7000](#) for Reztore® Surface & Mat Cleaner Application Instructions.

RoHS 3, REACH, and Conflict Minerals Statement

See the Desco Industries RoHS 3, REACH, and Conflict Minerals Statement: Descoindustries.com/ROHS.aspx

See the Desco Limited Warranty: Desco.Descoindustries.com/Limited-Warranty.aspx

See the Desco Disclaimer: Desco.Descoindustries.com/Disclaimer.aspx

Statfree S Plus™ Dissipative Homogeneous Vinyl

Specifications

Standard Document
ANSI/ESD S20.20

Meets Requirements of:
Flooring

Electrical Properties

Rtt Resistance:
Rtg Resistance:

Typical Values

< 1 x 10⁹ ohms
< 1 x 10⁹ ohms

Test Procedures/Method

ANSI/ESD STM7.1 and ESD TR53
ANSI/ESD STM7.1 and ESD TR53

Physical Properties

Construction:

Vinyl/Nitrile Floor Runner

Thickness:

0.375"

Color:**

Grey

Texture:**

Non-directional, heavy embossed, soil and abrasion resistant

Weight:

0.65 lbs/ft² (0.317g/cm²)

Tolerances:

Width +/- 0.250"

Length +/- 0.250" every 1 linear foot of running material.

Matting materials have a tendency to shrink slightly when first unrolled. In applications where length is critical, allow the material to relax for at least 4 hours before cutting to size. Always trim with a sharp knife or razor blade.

**Color and texture may vary between lots and mills

For Sizes and Item Numbers, [Click Here](#)



Made in the
United States of America

Specifications and procedures subject to change without notice

DESCO

STATFREE S PLUS™ FLOOR MAT, VINYL, HOMOGENEOUS, ANTI-FATIGUE, .375" (9.5MM)

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com
PHONE (909) 627-8178 FAX (909) 627-7449

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407
PHONE (781) 821-8370 FAX (781) 575-0172

MATERIAL
STATFREE S Plus
DRAWING PM-120

DATE:
February
2019